



VALARIS JU-92

(ENSCO 92)

Marathon Le Tourneau -116-C Jackup • Year in Service: 1982

■ CAPACITIES

Rotary Load:
900,000 lbs

Setback Load:
450,000 lbs

Liquid Capacity:
1,824 bbl

Bulk Cement:
4,200 cu ft

Bulk Barite:
5,050 cu ft

Potable Water:
1,294 bbl

Drill Water:
8,243 bbl

Diesel Fuel:
7,160 bbl

Base Oil:
1,000 bbl

Brine:
1,000 bbl

■ DRILLING EQUIPMENT

Derrick:
Dreco 170ft x 30ft x 30ft

Travelling Block:
National B-500; swivel: National P-650

Drawworks:
National 1320-UE 2,000 hp

Prime Movers:
(2) EMD 12-645-E9B x 2,500 hp
(1) EMD 12-645-8 Rootes Blown x 1,650 hp

Cementing Equipment:
Halliburton SKD-4-Unipro 2

Cranes:
(1) Dreco 48 DNS 120ft, 40.75Ton @ 40ft, (2) MLT PCM-120ft, 32Ton @ 40ft

Top Drive/Power Swivel:
Varco TDS-4H

Crown Block:
Dreco 583 st

Rotary:
National C-375

Emergency Generator
480V AC, 60 Hz, 350 kW

Torque Wrench/Spinner:
(1) NOV AR3200

■ WELL CONTROL

Diverter:
ABB Regan KFDJ x 2,000 psi.

Annular:
(1) Hydril GX 13 5/8" 5M

BOP:
(1) Cameron 13 5/8" 10M double
(1) Cameron 13 5/8" 10M single

■ MUD SYSTEMS

Mud Pumps:
(3) National 12-P-160 triplex x 1,600 hp

Shale Shakers:
(4) SWACO BEM 650

Degasser:
(1) Swaco 1,000 gpm

■ PRIMARY RIG CHARACTERISTICS

Maximum Water Depth:
210ft

Leg Length:
343ft

Hull Length:
243ft

Hull Width:
200ft

Hull Depth:
26ft

Maximum Drilling Depth:
25,000ft

Longitudinal Leg Centers:
129ft

Transverse Leg Centers:
142ft

Hook Load:
1,000,000 lbs

Cantilever Skid Out:
45ft

Substructure Travel:
12ft transverse to port or starboard

Mud System Max. Pressure:
5,000 psi

Quarters Accommodations:
90 persons

Heliport - can accommodate:
S-61

Changes / modifications to the above listed equipment could occur.

Maximum Water Depth denotes the designed rating, pending site specific assessment.

Should you have specific questions, please contact the Marketing Department at: marketing@valaris.com

REVISED 7/2019