



# VALARIS 67

(VALARIS JU-67)

Marathon LeTourneau Technologies 84-C Enhanced Jackup • Year in Service: 1976

## ■ CAPACITIES

Rotary Load:  
1,500,000 lbs

Setback Load:  
800,000 lbs

Liquid Capacity:  
2,550 bbl

Bulk Cement:  
3,120 cu ft

Bulk Barite:  
3,120 cu ft

Potable Water:  
1,294 bbl

Drill Water:  
4,638 bbl

Diesel Fuel:  
4,638 bbl

Base Oil:  
1,400 bbl

Brine:  
1,000 bbl

## ■ DRILLING EQUIPMENT

Derrick:  
Dreco 160ft x 30ft x 30ft

Travelling Block:  
National Oilwell 750 st

Drawworks:  
National 1625 DE 3,000 horsepower

Prime Movers:  
(3) EMD 16-645-E8 driving  
(1) EMD AB-20-N6 2,100 kW generator

Cementing Equipment:  
Schlumberger CPS 361, Dual Pump, 15,000 psi

Cranes:  
(2) LeTourneau PSM-120AS (1) Favelle Favco 7.5/10K

Top Drive/Power Swivel:  
Varco TDS-4H-750t and GE 752 motor

Crown Block:  
750 st

Rotary:  
National C-375

Emergency Generator  
(1) Cat D-379 driving  
(1) Kato 400 kW generator

Torque Wrench/Spinner:  
(1) Varco ST-120

## ■ WELL CONTROL

Diverter:  
GE-KFDJ - 37 1/2" x 2,000 psi

Annular:  
(1) Shaffer 13 5/8" 5M

BOP:  
(2) Cameron 13 5/8" 10M doubles

## ■ MUD SYSTEMS

Mud Pumps:  
(3) National 12-P-160

Shale Shakers:  
(4) Brandt VSM-300 Dual Deck Balanced Elliptical Motion

Degasser:  
Brandt 1,000 gpm

## ■ PRIMARY RIG CHARACTERISTICS

Max. Deployed Leg Length:  
447ft

Leg Length:  
511ft

Hull Length:  
237.8ft

Hull Width:  
227.5ft

Hull Depth:  
26ft

Maximum Drilling Depth:  
30,000ft

Longitudinal Leg Centers:  
142ft

Transverse Leg Centers:  
129ft

Hook Load:  
1,500,00 lbs

Cantilever Skid Out:  
60ft (with 10ft extensions)

Substructure Travel:  
15ft transverse to port or starboard

Mud System Max. Pressure:  
5,000 psi

Quarters Accommodations:  
110 persons

Heliport - can accommodate:  
Astech MI-17

Changes / modifications to the above listed equipment could occur.

Maximum Water Depth denotes the designed rating, pending site specific assessment.

Should you have specific questions, please contact the Marketing Department at: [marketing@valaris.com](mailto:marketing@valaris.com)